

Philips
Coaxial cable

6 ft

RG59 Right angle

SWV2212



Ensure a reliable connection

with this right angle type coaxial cable

Depend on this cable to provide you with a reliable audio/video connection between components.

Enjoy good picture quality

- Nickel-plated connectors for reliable contact

Enjoy good audio quality

- High purity copper conductor for reliable signal transfer

Protects against signal loss

- Bare copper shielding

Easy installation

- Non-slip ergonomic grip for easy use
- Plug and play for easy use

Enjoy extended durability

- Molded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

PHILIPS

sense and simplicity

Coaxial cable
6 ft RG59 Right angle

Specifications

Packaging

- EAN/UPC/GTIN: 6 09585 12295 6
- Quantity: 1
- Gross Weight: 0.120 kg
- Tare Weight: 0.010 kg
- Net Weight: 0.110 kg
- Length: 19.70 cm
- Width: 9.50 cm
- Height: 5.20 cm

Inner Carton

- EAN/UPC/GTIN: 1 06 09585 12295 3
- Quantity: 4
- Gross Weight: 0.470 kg
- Tare Weight: 0.040 kg

- Net Weight: 0.430 kg
- Length (cm): 20.60 cm
- Width (cm): 10.90 cm
- Height (cm): 17.20 cm

Outer Carton

- EAN/UPC/GTIN: 2 06 09585 12295 0
- Quantity: 48
- Gross Weight: 5.620 kg
- Tare Weight: 0.430 kg
- Net Weight: 5.190 kg
- Length (cm): 42.90 cm
- Width (cm): 35.10 cm
- Height (cm): 36.50 cm

SWV2212/17

Product highlights

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

Plug and play

Plug and play offers easy installation of components without time-consuming installations.

Bare copper shielding

Bare copper shielding protects against signal loss.

High purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.

Molded plug

Molded plugs ensure secure connections between components and offer extended durability.

Nickel-plated connectors

Nickel-plated connectors establish a clean contact between the cable and connector for a reliable connection.

Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Rubber strain relief

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.



Issue date 2007-12-08

Version: 1.0.5

12 NC: 8670 000 26043
UPC: 6 09585 12295 6

© 2007 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com